

KSG joint cutter type 460-II



- **Compact – Robust – User friendly**
- **Central loading lug**
- **Large ball-bearing wheels**

The KSG joint cutter model 460-II is particularly suitable for cutting of expansion joints as well as for bigger cutting jobs.

- Infinite setting of cutting depth via trapezoidal spindle
- Easy cutting wheel exchange without having to dismantle the cutting guard
- Exchange and tensioning of the V-belt with little effort
- Low water consumption thanks to central water supply
- Central loading lug
- Water supply from 20 litre water tank. External water connection is possible via quick coupler.

Technical data:

Motor type	HONDA-GX 390 gasoline	YANMAR L 100 diesel	HATZ 1 B 30 diesel
Motor output KW/HP	10 KW / 13 HP	7,5 KW / 10 HP	4,6 KW / 6,3 HP
Blade Φ max.	450 mm	450 mm	450 mm
Cutting depth	165 mm	165 mm	165 mm
Water tank	20 litres	20 litres	20 litres
Central loading lug	Yes	Yes	Yes
Dimensions L/B/H cm	113 x 50 x 118	113 x 50 x 118	113 x 50 x 118
Weight	95 kg	98 kg	98 kg
Special accessories	Adapter for expansion joints / blade protector for cutting right up along walls		

We reserve the right to make alterations in line with technical development.

KSG Maschinenbau GmbH
 Special machines for road construction
 D-66386 St.Ingbert | Am Schindwasen 14
 Tel. +49-6894-8108 | Fax +49-6894-381751
<http://www.ksg-cutcompact.de> | E-Mail : info@ksg-gmbh.de

Dealer stamp