

[Home](#) > [Tractors](#) > [4wd Track Tractors](#) > [9R 540 Tractor](#)



9R 540

Tractor

- Engine HP: 594 Max / 540 hp Rated
- AutoTrac™, StarFire™ receiver, and Gen 4 display integrated
- e18™ PowerShift Transmission
- Choice of three different cab and visibility packages

[Build Your Own](#)

[Find a Dealer](#)

[Request a Demo](#) >

Features

[Expand All](#)

- + PowerTech™ 13.6L (827-cu in.) engine: real world usability, not just power on paper

- + 9 Series Visibility packages let you run with confidence, dawn until dusk

- + Put more power to the ground, more comfortably, with the industry-exclusive HydraCushion™ suspension

- + In the field or on the road: adjust steering ratio on-the-go with ActiveCommand Steering (ACS™)

- + John Deere integrated solutions: a world of connected technology, right from the factory

- + Work at your best with 9 Series Comfort and Convenience packages

- + A range of hydraulic options give you the power and flexibility to take on your toughest applications

- + The new 9 Series: Easy to run, easy to maintain

Show Less

Specifications

Key Specs

Engine description

John Deere PowerTech™ 13.6L (B20 diesel compatible)

Engine displacement

13.6 L
827 cu in.

Rated engine power

397 kW
540 hp

Maximum engine power	437 kW 594 hp
Rated PTO power (hp SAE)	249 kW 335 hp
Transmission type	John Deere e18™ 18-speed PowerShift™ with Efficiency Manager™: 40 km/h 25 mph
Hydraulic pump rated output	Standard: 208 L/min 55 gpm Optional: 416 L/min 110 gpm
Rear hitch category (SAE designation)	Category 4N/4: 6804 kg 15,000 lb Category 4N/4: 9072 kg 20,000 lb
Base machine weight	20,856 kg 45,980 lb

Engine specifications

Description	John Deere PowerTech 13.6L (B20 diesel compatible)
Engine type	Diesel, inline, 6-cylinder, wet-sleeve cylinder liners with four valves in-head
Rated speed	2100 rpm
Aspiration	Dual series turbocharger with fixed geometry first stage and wastegated second stage; air-to-air aftercooling and cooled exhaust gas recirculation (EGR)
Emission level	Final Tier 4 (FT4)

After treatment type

Diesel oxidation catalyst (DOC)/selective catalytic reduction (SCR)

Displacement

13.6 L
827 cu in.

Engine performance

Rated power

397 kW
540 hp

Rated PTO power (hp SAE)

249 kW
335 hp

Power boost

10 percent

Maximum engine power

437 kW
594 hp

Engine peak torque

At 1600 rpm: 2492 Nm 1838 lb-ft

PTO torque rise

38 percent

Transmission

Type

John Deere e18 18-speed PowerShift with Efficiency Manager: 40 km/h
25 mph

Hydraulic system

Type

Closed-center, pressure-and-flow compensated

Pump rated output

Standard: 208 L/min

55 gpm

Optional: 416 L/min

110 gpm

Available flow at a single rear SCV

1.3-cm (1/2-in.) couplers: 132 L/min

35 gpm

1.9-cm (3/4-in.) couplers: 159 L/min

42 gpm

Number of rear selective control valves (SCVs)

Four to eight factory or field installed

Base: four 1.3-cm (1/2-in.) couplers

Optional: five to six 1.3-cm (1/2-in.) couplers factory installed

Optional: three 1.9-cm (3/4-in.) couplers plus five 1.3-cm (1/2-in.) couplers factory installed

SCV control

Electronic

Rear hitch**Hitch category (SAE designation)**

Category 4N/4: 6804 kg

15,000 lb

Category 4N/4: 9072 kg

20,000 lb

Maximum lift capacity behind lift points

Category 4N/4: 9072 kg

20,000 lb

Sensing type

Electrohydraulic with draft sensing

Drawbar**Drawbar category**

Category 5

Maximum vertical load

5440 kg
12,000 lb

Rear power take-off (PTO)

Type

Independent
44 mm (1.75 in.) 20-spline, 1000 rpm

PTO actuation

Electrohydraulic

Rear axle

Type

Diameter: 120 x 3048 mm
4.72 x 120 in.

Final drive type

Inboard planetary with double-reduction axle

Rear differential lock

Full-locking electrohydraulic

Front axle

Type

Diameter: 120 x 3048 mm
4.72 x 120 in.

Front axle differential lock

Full-locking electrohydraulic

Tires

Turning radius with brakes

Group 47 or Group 48 tires: 6.035 m
19.8 ft

Steering

Type

Standard: Hydraulic power steering
 Optional: ActiveCommand Steering (ACS™)

Electrical system

Alternator size

Standard: 250 amp
 Optional: 330 amp

Battery options

12 V

Working lights

Standard: 18 halogen
 Optional: 18 or 24 LED plus 8 LED convenience lights

**Type of bulb in headlight
(Halogen, Xenon, LED)**

Standard: halogen, 65 W
 Optional: LED

Total cold cranking amps

3 x 925 CCA
 Total: 2775 CCA

Operator station

Seat

Degree of seat swivel, left hand
 25 degree (angle)
 Degree of seat swivel, right hand
 40 degree (angle)
 Standard: air suspension
 Optional: ActiveSeat™ II

Instructional seat

Standard

Display

Standard: Generation 4 4600 CommandCenter™: 25.4 cm
 10 in.
 Optional: Extended monitor

Radio

Standard: AM/FM stereo with weatherband, remote controls, auxiliary input jack, four speakers and external antenna

Optional: Touchscreen radio

Inner cab volume

3.27 m³

115 cu ft

Cab glass area

6.64 m²

71.47 sq ft

Dimensions

Wheelbase

3912 mm

154 in.

Overall length

With front weights, excluding hitch and coupler: 7945 mm

312.8 in.

With front weights, including hitch and coupler: 8427 mm

331.8 in.

Drawbar clearance

Group 48 tires: 527 mm

20.7 in.

Approximate shipping weight, Open;Cab

20,856 kg

45,980 lb

Weight

Base machine weight

20,856 kg

45,980 lb

Maximum ballast level

27,216 kg

60,000 lb

Capacities

Crankcase oil volume

64 L
16.9 U.S. gal.

Fuel tank

1514 L
400 U.S. gal.

Diesel exhaust fluid (DEF) tank

120 L
31.7 U.S. gal.

Cooling system

56.5 L
14.9 U.S. gal.

Transmission-hydraulic system

With 3-point hitch and PTO: 227 L
60 U.S. gal.
Without 3-point hitch and PTO: 220 L
58 U.S. gal.

Serviceability

Interval for engine oil change

500 hours

Interval for

1500 hours

Interval for engine coolant

6000 hours

Precision AG

Guidance

Integrated AutoTrac™

Telematic

Available with JDLink™ hardware, activations, and Ethernet harnesses (availability dependent upon destination)

Remote diagnostics

Available with activated JDLink hardware and activations

Miscellaneous

Country of manufacture

USA

Additional information

Date collected

1 March 2021

Show Less

Accessories and Attachments

Expand All

Cab Operator's Station

- + Accessory Mounting Bracket - 9330RWRE343680
- + Cell Phone Mount Kit - 9330RWBRE10015
- + Clamp Style Mount - 9330RWAXE59372
- + CommandARM™ Bracket - 9330RWBRE10501
- + Fire Extinguisher, Wheel and 4 Track - 9330RWBRE10242
- + Floor insulation - 9330RWBRE10202
- + Foot rests - 9330RWBRE10458
- + Foot-Operated Speed Control - 9330RWBRE10440
- + Hook, Harness Routing - 9330RWR562310

-
- + Leather Wrapped Steering Wheel - 9330RWRE584990
-
- + RAM 1 inch T-slot Ball Mount - 9330RWBRE10482
-
- + RAM 1.5 inch T-slot Ball Mount - 9330RWBRE10483
-
- + Refrigerator - 9330RWRE593672
-
- + Right Window Mounting Bracket and Rail - 9330RWBRE10465
-
- + Secondary Hitch Controls - 9330RWBRE10437
-
- + Self - Leveling Cup Holder - 9330RWBRE10152
-
- + Short Vertical Mounting Rail - 9330RWBRE10464
-
- + StarFire 6000 Locking Bracket - 9330RWBPF11074
-
- + Storage Container with Lid/Ash Tray - 9330RWRE275532
-
- + Sunshade - 9330RWRE593670
-
- + Tablet Mount Kit - 9330RWBRE10255
-

Connectivity Hardware

-
- + Front Implement CAN Communication Connector - 9330RWRE344751
-
- + ISO Cab Implement CAN Bus Adapter - 9330RWRE322780
-
- + Mounting Bracket, Universal StarFire™ - 9330RWRE588540
-
- + RTK Bracket Kit - 9330RWBRE10512
-

DISPLAY HARDWARE

-
- + Display Harness - GS2 / GS3 Display with Video to GreenStar™ (Round) Cornerpost 762 mm (30 in.) - 9330RWFP12435
-
- + Ethernet Adapter Cable (Square to Round) 800 mm (2.5 ft) - 9330RWFP12950
-
- + GreenStar™/Gen4 - 254 mm (10 in.) Display Touch Panel Protector Service Kit - 9330RWPF90596
-
- + Harness - Original GreenStar™ Display and Mobile Processor to GreenStar™ 3 or GreenStar™ 2 (Round) Cornerpost - 9330RWPF90686
-

Drawbar

-
- + Drawbar, Ball-type 80 mm, Category 4 - 9330RWRE283958
-
- + Scraper Hose Support - 9330RWBRE10164
-

Electrical

-
- + 3-pin octagonal to 3-pin round convenience outlet (flat pins) single device adapter - 9330RWRE596959
-
- + 6-outlet octagonal powerstrip with pre-installed round convenience outlet (flat pins) - 9330RWRE596958
-
- + 9-Pin Connector for Implement Feedback - 9330RWRE67685
-
- + Electrical Connector Assembly, Power Inverter Kit 120VAC/60HZ 300 Watt - 9330RWBRE10452
-
- + Harness adapter for CB power connection - 9330RWRE597710
-

Hydraulic Selective Control Valves (SCVs)

+ 3/4 In. Selective Control Valve Coupler Kit (Hi-Flow only) - 9330RWBRE10107

+ 3/4 Inch Coupler Adapter Conversion - 9330RWBRE10486

+ 5th and 6th Scraper High Flow Remote Cylinder Selective Control Valve with Breakaway Couplers - 9330RWBRE10109

+ Add 5th or 6th Remote Selective Control Valves - 9330RWBRE10168

Hydraulics

+ Hitch Auxiliary Raise Kit DR - 9330RWBRE10203

+ Motor Case Drain Kit, DR Wheel - 9330RWBRE10113

+ Power Beyond Coupler Kit 1/2 In. - 9330RWBRE10110

+ Power Beyond Coupler Kit 3/4 In. - 9330RWBRE10111

Lighting

+ LED Rear Light Kit - 9330RWBRE10446

+ LED Roof Mounted Light Kit - 9330RWBRE10445

Mirrors

+ External Mirrors Conversion Kit, Electrically Adjustable (Wide Angle) - 9330RWBRE10477

+ Rear View Mirror (Internal) - 9330RWRE588734

Radio

- + Auxiliary Camera Input Kit for Touch Screen Radio - 9330RWBRE10502
 - + Subwoofer and Tweeter Kit - 9330RWBRE10451
 - + Touchscreen Radio Relocation kit (Alternative Mount) - 9330RWBRE10364
-

Rear Hitch

- + Category 4N/3 Quik Coupler Kit - 9330RWRE270270
 - + Category 5 to Category 4 Drawbar Conversion Kit - 9330RWRE278847
 - + Electro-Hydraulic 3 Point Hitch, DR for wheel and 4 Track Tractors - 9330RWBRE10160
 - + Rear Hitch Heavy Duty Greaseable Pin Kit - 9330RWBRE10332
-

Transmission

- + Back Up Alarm Kit - 9330RWRE273380
 - + Mounting Kit - Dual Beam Radar Sensor, Wheels - 9330RWRE269592
 - + Radar with Dual Beam Sensor - NA - 9330RWRE278980
-

Weights

- + Center Link Bracket for Monoblock - 9330RWBL15085
 - + Pick Up Weight 1500 kg (3307 lb) Monoblock - 9330RWBL15020
-

+ Pick Up Weight 900 kg (1984 lb) Monoblock - 9330RWBL15083

+ Weight, front suitcase 43 kg (95 lb) quantity of one - 9330RWR127764

Wheel Weights

+ Starter Weight, Wheel, 72 kg (159 lb) - 9330RWR167153

+ Weight, Wheel 205 kg (452 lb) - 9330RWR207782

+ Weight, Wheel 625 kg (1378 lb) - 9330RWR553540

+ Weight, Wheel Kit 2x205 kg (2x452 lb) - 9330RWBL15076

+ Weight, Wheel Kit 2x205 kg (Weights), 2x72 kg (Adapter Weights) - 9330RWBL15071

Wheels and Hubs

+ Rear Dual Hub Extension, 127 mm (5 in.) - 9330RWAR194744

+ Rear Dual Hub Extension, 254 mm (10 in.) - 9330RWAR190666

+ Rear Dual Hub Extension, 330 mm (13 in.) - 9330RWAR190668

+ Rear Dual Hub Extension, 381 mm (15 in.) - 9330RWAR190669

[Show Less](#)

Shop and Buy

[Build Your Own](#)

Maintenance and Support

[Service Info](#)

**You May Also Be
Interested In**

[Buy Online](#)

[Product Safety](#)

[John Deere Rewards](#)

[Buy Parts](#)

[Used Equipment](#)

[Find a Dealer](#)

[View California Products](#)

[John Deere Financial](#)

Product features are based on published information at the time of publication. Product features are subject to change without notice. Contact your local John Deere dealer for more information.