



EQUIPMENT AND ACCESSORIES

Manufacturer				TAILIFT	TAILIFT	TAILIFT	TAILIFT	TAILIFT	TAILIFT
Model				FD60	FD70	FD80	FD100	FG60	FG70
Capacity		Kg		6000	7000	8000	10000	6000	7000
Load center		mm		600	600	600	600	600	600
Power type				Diesel	Diesel	Diesel	Diesel	Gasoline	Gasoline
Tires	S=Solid	P=Pneumatic	front/rear	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic	Pneumatic
Total width		A	mm	2010	2010	2060	2170	2010	2010
Height mast lowered		h1	mm	2500	2625	2700	2850	2500	2625
Overhead guard height		h6	mm	2450	2450	2520	2540	2450	2450
Height mast extended		h4	mm	4420	4420	4420	4420	4420	4420
Total length		R	mm	4755	4815	5410	5625	4755	4815
Tires	Number (front/rear, X Driven)			4X/2					
	Size	Front	AA	8.25-15-14PR	8.25-15-14PR	8.25-20-14PR	9.00-20-14PR	8.25-15-14PR	8.25-15-14PR
		rear	AB	8.25-15-14PR	8.25-15-14PR	9.00-16-14PR	9.00-20-14PR	8.25-15-14PR	8.25-15-14PR
Engine	Model			Perkins1106D	Perkins1106D	Perkins1106D	Perkins1106D	GM 4.3L	GM 4.3L
	Rated Power		kw/rpm	117/2200	117/2200	117/2200	117/2200	122/4000	122/4000
	Rated torque		N.m./rpm	683/1400	683/1400	683/1400	683/1400	2500	2500
	Number of cylinders/Displacement		L	6 / 6.6	6 / 6.6	6 / 6.6	6 / 6.6	6/4300	6/4300
Trans- mission	Type			HYDRAULIC					
	Speed rank of transmission rear/front			2 / 2					



TAI PIIN INDUSTRIAL CO.,LTD.

No. 269, Sec 1, Shein Lin Rd., Taichung, Taiwan. (R.O.C.) TEL:+886-4-25666100 FAX:+886-4-25671670
 Website: <http://www.atrison.com.tw> E-mail: insales@atrison.com.tw

DOC. S/N:DEB033 EDITION:01