



# EISEMANN

## H 13000E

Order Number 087134

Tank in modular design 1 three-phase current CEE socket (32 A) 1 alternative current CEE socket (32A) running time counter 1 protective contact socket (16 A) 4-pol. therm./magnet. cutout. Delivery without battery.



Attribute	Unit	Value
Genset type		Synchronous
Electrical capacity (3~) cos $\phi$ 0,8	VA	13000
Electrical capacity (1~) cos $\phi$ 0,8	VA	9660
Voltage (3~)	V	400
Voltage (1~)	V	230
Current (3~)	A	18.6
Maximum sum. current (1~)	A	42
Current (CEE 1~)	A	26
Current (Schuko 1~)	A	16
Starting current	A 3~	28
Starting current	A 1~	55
Frequency	Hz	50
Protection		IP 54
Engine type		Briggs&Stratton 386447
Cylinders		2
Speed	U min <sup>-1</sup>	3000
Fuel type		Petrol
Engine oil capacity	l	1.7
Engine power	kW	13.8
Cooling	engine / generator	air / air
Fuel capacity	l	2 x 10
Operation time 3/4 load	h	5.7
Weight	kg	130
Dimensions	mm	790 x 550 x 650
Acoustic power	dB(A)	98
Acoustic pressure	dB(A)	70

Related equipment	Order Number	Related equipment	Order Number
Exhaust hose, 904872	904872	Universal onboard-computer UBC, 908254	908254
Remote starting, 908257	908257	Earthing set, 908250	908250
Isolation control device, with cut-off, accordi ...	018521	Chassis, 988548	988548
Lifting set, 911643	911643	Professional light pole, 908510	908510
Blackout - Control BLC100, 3ph., 988315	988315	Emergency power change-over, 3ph., 988332	988332
Additional fuel tank, 50l, 923995	923995	Additional fuel tank, 100l, 923998	923998
Additional fuel tank, 150l, 923963	923963	Starterbatterie 020316	020316
Gas-kit, on demand	auf Anfrage		

GEKO

EISEMANN

Metallwarenfabrik Gemmingen GmbH  
Industriestrasse 1 D-75050 Gemmingen

Telefon +49 (0) 7267 806-0  
www.metallwarenfabrik.com

Fax +49 (0) 7267 806-100  
info@metallwarenfabrik.com