

# Technical Specifications

Model	RF 3325R	RF 3325 SC14	RF 3325 SC25
<b>Weight and dimensions</b>			
Length (m)	4.10	4.10	4.10
Width (m)	2.52	2.52	2.52
Height (m)	2.30	2.30	2.30
Weight (kg)	2840	3040	
<b>Bale chamber</b>			
Rollers (nb)	17	17	17
Diameter (m)	1.25	1.25	1.25
Width (m)	1.20	1.20	1.20
Bale ramp	o	o	o
<b>Pick-up</b>			
Working width (cm)	220	220	220
Number of tine rows	5	5	5
Tine spacing (mm)			
Short crop device	Roller crop press	Roller crop press	Roller crop press
Pneumatic gauge wheels	•	•	•
AutoLevel Pick-up	-	-	o
<b>Intake</b>			
SuperFeed Rotor	•	-	-
SuperCut 14 knives	-	•	-
SuperCut 25 knives	-	-	•
Single knife protection	-	•	•
Knife group selection	-	-	•
Drop floor	•	•	•
<b>Driveline</b>			
11/4" chains	•	•	•
W-A PTO shaft	•	•	•
Cam clutch protection	•	•	•
Central. greasable roller bearings	•	•	•
<b>Binding</b>			
Twine (double) / Capacity (m)	•	-	-
Net / Capacity (m)	o	•	•
Net & Twine / Capacity (m)	o	o	-
<b>Operations</b>			
Focus	•	•	•
Hydraulic outlets	2SA	2SA	2SA
<b>Wheels and Axles</b>			
11.5/80-15	•	-	-
15.0/55-17	o	•	•
19.0/45-17	o	o	o
500/45-22.5	-	o	o
Hydraulic brakes	-	o	o
Pneumatic brakes	-	o	o
<b>Others</b>			
Drawbar	•	•	•
PTO (rpm)	540	540	540
Min. power requirem. (kW/hp)	51/70	59/80	73/100

• = Standard Equipment o = Optional Equipment - = Not available