

8 BRUTE FORCE KFX





Outmuscle the outdoors with capability at your disposal. Kawasaki Brute Force® ATVs are powerfully equipped to endure nature's most difficult challenges. When the going gets tough, step up with brute force.



Kawasaki side x sides, ATVs and Jet Ski® watercraft are assembled by Kawasaki Motors Manufacturing Corp., U.S.A. from foreign and domestic parts in Lincoln, NE.

*Assembled in the U.S.A. badge applies to Brute Force® 750 4x4i models only.



TAKE CHARGE BRUTE FOR CE 750 4x4i







DOMINATING POWER

The fuel-injected 749cc V-twin engine pumps out strong low-rpm torque for incredible acceleration, while precise fuel metering allows for easy starting and optimum fuel mileage.



CVT & DRIVE

An automatic Continuously Variable
Transmission (CVT) plays a key role within the
Kawasaki Automatic Power-Drive System (KAPS)
to provide smooth power during low-speed
operation and strong acceleration into higher
rpm. Selectable drive modes allow you to switch
from 2WD to 4WD at the press of a button.



CHASSIS

Durability and strength are the result of a reinforced double-cradle frame. Independent suspension smooths out rough terrain with pre-load adjustable shocks.



RUGGED CAPABILITY

Navigate rugged trails with a tight turning radius and 9.4 inches of ground clearance. For the homesteader, the Brute Force® 750 4x4i ATV is an exceptional choice, featuring a robust 1,250-pound towing capacity. Bring all of your gear along for the ride with 88 pounds of front cargo rack capacity and 176 pounds of rear cargo rack capacity.







Candy Steel Furnace Orange (Premium Paint Finish) Super Black Vibrant Blue

BRUTE FORCE® 750 4x4i EPS

• Speed-sensitive Electric Power Steering (EPS)

Standard Features

- 749cc, V-twin, 4-stroke Engine
- · Selectable 2WD/4WD Drive Modes
- · Independent 4-wheel Suspension
- · Front and Rear Cargo Racks



Realtree Xtra® Green Camo

BRUTE FORCE® 750 4x4i EPS CAMO

Trim Features

- · Speed-sensitive Electric Power Steering (EPS)
- · Realtree Xtra® Green Camo Bodywork

Standard Features

- · 749cc, V-twin, 4-stroke Engine
- · Selectable 2WD/4WD Drive Modes
- Independent 4-wheel Suspension
- Front and Rear Cargo Racks



Realtree Xtra® Green Camo—Realtree APG-XTRA Camouflage Design
© 2012 of Jordan Outdoor Enterprises, Ltd., GREEN all rights reserved.



Firecracker Red

BRUTE FORCE® 750 4x4i

Standard Features

- 749cc, V-twin, 4-stroke Engine
- · Selectable 2WD/4WD Drive Modes
- · Independent 4-wheel Suspension
- · Front and Rear Cargo Racks

BUILT TO PERFORM BRUTE FORCE 300

For tackling tasks or exploring trails, the Brute Force® 300 ATV is distinguished by versatility. A reliable 271cc engine, nimble handling with low-effort steering and excellent build quality make it a capable and competent outdoor companion.



COMPACT POWER

Smooth and responsive power is produced by a 271cc single-cylinder engine and efficient automatic Continuously Variable Transmission (CVT). For the outdoor adventurer or the busy homesteader, the Brute Force® 300 ATV is the ideal companion.

UNPARALLELED MANEUVERABILITY

The Brute Force® 300 ATV comes equipped with a durable centrifugal clutch designed to withstand the elements. Consistent power delivery allows for smooth acceleration and seamless engine braking.







CAPABLE | CHASSIS

Brute Force® 300 ATVs are built around a strong and durable double cradle steel-tube frame which helps provide outstanding straight-line performance and responsive handling. Independent A-arms in the front and a single shock and swingarm in the rear soak up bumps over rough, uneven terrain to produce a smooth ride.



CARGO AND TOWING

For this compact workhorse, versatility means the ability to tow 500 pounds while hauling up to 44 and 66 pounds on the front and rear cargo racks, respectively.



BRUTE FORCE® 300

- 271cc Liquid-cooled, 4-stroke Engine
- Continuously Variable Transmission (CVT) with HI/LO Ranges and Reverse with Centrifugal Clutch
- · Front and Rear Cargo Racks
- 500-lb. Towing Capacity













SUSPENSION

Smooth and sporty suspension performance is produced by independent front A-arms and a single shock and swingarm in the rear. At higher speeds, the KFX®90 ATV exhibits agile performance and capable handling which riders with more experience can appreciate.



ELECTRIC START

An electric start gets the KFX®90 ATV going with the push of a button. Young riders will experience more independence on the track, while a keyed ignition deters unauthorized use. For backup, a kick-start comes standard.



KFX®90

- 89cc 4-stroke Engine and Automatic Transmission
- Electric Start for Simple and Reliable Starting
- Adjustable Throttle Limiter and Continuously Variable Transmission (CVT) Collar Allows Speed and Performance to be Adapted to Rider Experience
- · Keyed Ignition Helps Prevent Unauthorized Use
- Single Shock Rear Suspension and Independent A-arm Front Suspension Contribute to Sporty Handling









POWERFUL BRAKES

Two front drum brakes and a rear disc brake provide ample stopping power. All brakes use handlebar-mounted levers. Full-length floorboards help protect feet.



PARENTAL CONTROLS

A keyed ignition allows parents to supervise the start of the vehicle. A throttle limiting screw restricts throttle opening, so the power level can be matched to the skill level of the rider. A collar in the CVT can easily be removed for increased performance as riders gain experience and confidence.



KFX®50

- 49.5cc 4-stroke Engine and Automatic Transmission
- Electric Start for Simple and Reliable Starting
- Adjustable Throttle Limiter and Continuously Variable Transmission (CVT) Collar Allows Speed and Performance to be Adapted to Rider Experience
- Keyed Ignition Helps Prevent Unauthorized Use
- Single Shock Rear Suspension and Independent A-arm Front Suspension Contribute to Sporty Handling



KFX°50 in Lime Green







RRHITE		

BRUTE FORCE® 750 4x4i EPS CAMO

BRUTE FORCE® 750 4x4i

ENGINE DISPLACE MAXIMUM FUEL SYS' TRANSMIS FINAL DRI		4-stroke, V-twin, SOHC, liquid-cooled	4-stroke, V-twin, SOHC, liquid-cooled	4-stroke, V-twin, SOHC, liquid-cooled
DISPLACE	MENT	749cc	749cc	749cc
MAXIMUM	1 TORQUE	42.7 lb-ft @ 4750 rpm	42.7 lb-ft @ 4750 rpm	42.7 lb-ft @ 4750 rpm
FUEL SYS	TEM	DFI® with two 36mm throttle bodies	DFI® with two 36mm throttle bodies	DFI® with two 36mm throttle bodies
TRANSMIS	SSION	Automatic CVT (H,L,N,R)	Automatic CVT (H,L,N,R)	Automatic CVT (H,L,N,R)
FINAL DRI	IVE	Selectable 2WD/4WD with variable control front differential lock, shaft	Selectable 2WD/4WD with variable control front differential lock, shaft	Selectable 2WD/4WD with variable control front differential lock, shaft
FRONT SUSPENS WHEEL TE		Double wishbone/6.7 in	Double wishbone/6.7 in	Double wishbone/6.7 in
REAR SUS / WHEEL	SPENSION TRAVEL	Double wishbone/7.5 in	Double wishbone/7.5 in	Double wishbone/7.5 in
FRONT TII	RE	AT 25 x 8-12	AT 25 x 8-12	AT 25 x 8-12
REAR TIRE	E	AT 25 x 10-12	AT 25 x 10-12	AT 25 x 10-12
FRONT BE	RAKES	Dual hydraulic 176mm discs with 2- piston calipers	Dual hydraulic 200mm discs with 2- piston calipers	Dual hydraulic 200mm discs with 2- piston calipers
REAR BRA	AKES	Sealed, oil-bathed, multi-disc with independent park brake	Sealed, oil-bathed, multi-disc with independent park brake	Sealed, oil-bathed, multi-disc with independent park brake
TURNING	RADIUS	10.5 ft	10.5 ft	10.5 ft
LIGHTING	i	35W headlights, 5W taillight, 21W stoplight	35W headlights, 5W taillight, 21W stoplight	35W headlights, 5W taillight, 21W stoplight
ELECTRON POWER ST (EPS)		Yes	Yes	No
GROUND		9.4 in	9.4 in	9.4 in

GROUND CLEARANCE	9.4 in	9.4 in	9.4 in
FUEL CAPACITY	5.0 gal	5.0 gal	5.0 gal
TOWING CAPACITIY	1250 lb	1250 lb	1250 lb
TOTAL RACK CAPACITY	242.0 lb	242.0 lb	242.0 lb
RACK CAPACITY, FRONT/REAR	88.0/176.0 lb	88.0/176.0 lb	88.0/176.0 lb
OVERALL LENGTH	86.4 in	86.4 in	86.4 in
OVERALL WIDTH	46.5 in	46.5 in	46.5 in
OVERALL HEIGHT	48.0 in	48.0 in	48.0 in
SEAT HEIGHT	35.8 in	35.8 in	35.8 in
CURB WEIGHT	699.0 lb**	699.0 lb**	688.0 lb**
WHEELBASE	50.6 in	50.6 in	50.6 in
WARRANTY	12 Month Limited Warranty	12 Month Limited Warranty	12 Month Limited Warranty
KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	12, 24, 36, or 48 months	12, 24, 36, or 48 months
	CLEARANCE FUEL CAPACITY TOWING CAPACITIY TOTAL RACK CAPACITY RACK CAPACITY, FRONT/REAR OVERALL LENGTH OVERALL WIDTH OVERALL HEIGHT SEAT HEIGHT CURB WEIGHT WHEELBASE WARRANTY KAWASAKI PROTECTION	CLEARANCE FUEL CAPACITY 5.0 gal TOWING CAPACITIY 1250 lb TOTAL RACK 242.0 lb CAPACITY RACK CAPACITY, FRONT/REAR OVERALL LENGTH 86.4 in OVERALL WIDTH 46.5 in OVERALL HEIGHT 48.0 in SEAT HEIGHT 35.8 in CURB WEIGHT 699.0 lb** WHEELBASE 50.6 in WARRANTY 12 Month Limited Warranty KAWASAKI 12, 24, 36, or 48 months PROTECTION	CLEARANCE FUEL CAPACITY 5.0 gal 5.0 gal TOWING CAPACITIY 1250 lb 1250 lb TOTAL RACK CAPACITY 242.0 lb 242.0 lb RACK CAPACITY, FRONT/REAR 88.0/176.0 lb 88.0/176.0 lb OVERALL LENGTH 86.4 in 86.4 in OVERALL WIDTH 46.5 in 46.5 in OVERALL HEIGHT 48.0 in 48.0 in SEAT HEIGHT 35.8 in 35.8 in CURB WEIGHT 699.0 lb** 699.0 lb** WHEELBASE 50.6 in 50.6 in WARRANTY 12 Month Limited Warranty 12 Month Limited Warranty KAWASAKI PROTECTION 12, 24, 36, or 48 months 12, 24, 36, or 48 months

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Realtree Xtra® Green Camo — Realtree APG-XTRA Camouflage Design® 2012 of Jordan Outdoor Enterprises, Ltd., all rights reserved.

Specifications subject to change; full specifications available on Kawasaki.com.



BRUTE FORCE® 300

<u> </u>	ENGINE	4-stroke, 1-cylinder, SOHC
IR.	DISPLACEMENT	271cc
RIVE	MAXIMUM TORQUE	15.9 lb-ft @ 6500 rpm
	FUEL SYSTEM	Keihin CVK32 carburetor
ENGINE AND DRIVETRAIN	TRANSMISSION	Automatic CVT with centrifugal clutch (H,L,N,R)
	FINAL DRIVE	2WD, Shaft

	FRONT SUSPENSION / WHEEL TRAVEL	Independent double wishbone/5.2 in
	REAR SUSPENSION / WHEEL TRAVEL	Swingarm/5.6 in
	FRONT TIRE	AT 22 x 7-10 Maxxis tubeless
CHASSIS	REAR TIRE	AT 22 x 10-10 Maxxis tubeless
	FRONT BRAKES	Dual 180mm discs
	REAR BRAKES	Single 180mm disc
	TURNING RADIUS	9.2 ft
	LIGHTING	(2) 35W headlights, 5W taillight and 21W stoplight
	ELECTRONIC POWER STEERING (EPS)	No

	GROUND CLEARANCE	6.1 in
S	FUEL CAPACITY	3.2 gal
	TOWING CAPACITIY	500 lb
	TOTAL RACK CAPACITY	110 lb
DIMENSIONS AND CAPABILITIES	RACK CAPACITY, FRONT/REAR	44/66 lb
CAP	OVERALL LENGTH	75.4 in
물	OVERALL WIDTH	42.5 in
SI SI	OVERALL HEIGHT	46.1 in
	SEAT HEIGHT	33.3 in
	CURB WEIGHT	535.8 lb**
	WHEELBASE	45.9 in
	WARRANTY	12 Month Limited Warranty
	KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Specifications subject to change; full specifications available on Kawasaki.com.









KFX [®] 90 K

Z	ENGINE	4-stroke, air-cooled, single	4-stroke, air-cooled, single
ETRAI	DISPLACEMENT	89.0cc	49.5cc
AND DRIVE	MAXIMUM TORQUE	N/A	N/A
A	FUEL SYSTEM	Mikuni PTE 16	Keihin PTE 16
ENGINE	TRANSMISSION	Automatic CVT	Automatic CVT
品	FINAL DRIVE	2WD, Chain	2WD, Chain

	FRONT SUSPENSION / WHEEL TRAVEL	Single A-arm/2.8 in	Single A-arm/2.8 in
	REAR SUSPENSION / WHEEL TRAVEL	Swingarm/2.9 in	Swingarm/2.9 in
	FRONT TIRE	AT 18 x 7-8 tubeless	AT 16 x 8-7 tubeless
200	REAR TIRE	AT 18 x 9-8 tubeless	AT 16 x 8-7 tubeless
CIIAoolo	FRONT BRAKES	Dual mechanical drums	Dual mechanical drums
ر	REAR BRAKES	Hydraulic disc	Hydraulic disc
	TURNING RADIUS	8.7 ft	8.7 ft
	LIGHTING	N/A	N/A
	ELECTRONIC POWER STEERING (EPS)	No	No

	GROUND CLEARANCE	At rear axle - 3.9 in	At rear axle - 3.3 in
	FUEL CAPACITY	1.5 gal	1.5 gal
	TOWING CAPACITIY	N/A	N/A
<u>S</u>	TOTAL RACK CAPACITY	N/A	N/A
DIMENSIONS AND CAPABILITIES	RACK CAPACITY, FRONT/REAR	N/A	N/A
5	OVERALL LENGTH	56.1 in	55.1 in
¥.	OVERALL WIDTH	35.6 in	34.7 in
<u> </u>	OVERALL HEIGHT	36.4 in	35.8 in
	SEAT HEIGHT	25.6 in	25.0 in
	CURB WEIGHT	266.8 lb**	245.0 lb**
	WHEELBASE	38.0 in	38.0 in
	WARRANTY	12 Month Limited Warranty	12 Month Limited Warranty
	KAWASAKI PROTECTION PLUS™ (OPTIONAL)	12, 24, 36, or 48 months	12, 24, 36, or 48 months

^{**}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

Specifications subject to change; full specifications available on Kawasaki.com.







CYCLE CITY CORP KAWASAKI

634 J CLYDE MORRIS BLVD, NEWPORT NEWS, VA 23601

PHONE: (757) 595-9721 **FAX:** (757) 595-9725

SUNRISE KAWASAKI

1559 E LITTLE CREEK RD, NORFOLK, VA 23518 **PHONE:** (757) 583-2223 **FAX:** (757) 588-0813

CYCLE WORLD KAWASAKI

4972 VIRGINIA BEACH BLVD, VIRGINIA BEACH, VA 23462

PHONE: (757) 499-4146 **FAX:** (757) 499-0493

WWW.VBCYCLEWORLD.COM

ASKEW KAWASAKI

1161 US HIGHWAY 17 S, ELIZABETH CITY, NC 27909 **PHONE:** (252) 338-1612 **FAX:** (252) 338-1879

WWW.ASKEWSCYCLES.COM

LIMITED WARRANTY

Your new Kawasaki ATV comes with a 12-month limited warranty.

UP TO FOUR YEARS ADDITIONAL COVERAGE

Let Kawasaki protect your new ATV for years to come with Kawasaki Protection Plus™. This plan repairs or replaces covered components free of charge if found defective in material or workmanship. Everything about the plan is easy. There's no deductible. It's honored at every authorized Kawasaki dealer nationwide. It's transferable to another owner with no fee. Just ask your dealer how you can buy additional coverage of 12, 24, 36 or 48 months, depending on the model and plan purchased. FL Lic #65500, Kawasaki Motors Corp., U.S.A., PO Box 25252, Santa Ana, CA 92799, (949) 770-0400.

KAWASAKI CARES

Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki's KFX®50 is recommended for use only by persons 6 or older, and the KFX®90 is recommended for use only by persons 12 and older. All children under 16 riding ATVs should always have direct adult supervision. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1 (800) 887-2887, or go to www.atvsafety.org.

©2019 Kawasaki Motors Corp., U.S.A.



Kawasaki subscribes to the guidelines of Tread Lightly!® a program dedicated to protecting the great outdoors through education and fostering responsible enjoyment of public lands.



*Assembled in the U.S.A. badge applies to Brute Force® 750 4x4i models only

All trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Printed in U.S.A. 99969-3785

