

PRODUCT SPECIFICATIONS FOR AP1055F

WEIGHTS

Operating Weight - With SE60 V	20452 kg
Tractor Operating Weight	17031 kg
Operating Weight - With SE60 VT XW	21918 kg
Tractor Shipping Weight	16691 kg
Operating Weight - With SE60 V XW	21128 kg

OPERATING SPECIFICATIONS

Standard Paving Range	3 - 6 m (9' 10"-19' 6")
Maximum Travel Speed	14.5 km/h
Inside Turn Radius	0.5 m
Hopper Capacity - Standard Entry	7.6 m ³
Maximum Paving Speed - With Tamper Bar Screed	25 m/min
Maximum Paving Speed - With Vibratory Screed	64 m/min
Maximum Paving Width - SE60 V Screed	7.65 m
Maximum Paving Width - SE60 V XW, VT XW Screeds	10 m
Hopper Capacity - Low Entry Hopper	8.1 m ³
Maximum Throughput Capacity	1602 tonnes/hr

DIMENSIONS

Operating Width - Standard Entry Hopper	3350 mm
Operating Height - Without Canopy	3715 mm

Operating Width - Low Entry Hopper	3604 mm
Operating Height - With Canopy	4000 mm
Transport Width - With End Gates Folded	3 m
Transport Width - With Screed End Gates	3.21 m
Truck Entry Height - With Low Entry Hopper	521 m
Truck Entry Height - With Standard Entry Hopper	572 mm
Transport Length - With SE60 V Screed	6.7 m
Transport Length - With SE60 XW-Series	6.88 m
Operating Length - With SE60 V Screed	6.86 m
Operating Length - With SE60 V XW, VT XW Screeds	7.05 in
Transport Height - Without Canopy	2.92 m
Transport Height - Canopy Retracted	3.05 mm

ENGINE

Gross Power	168 kW
Engine Model	Cat C7.1 with ACERT

SERVICE REFILL CAPACITIES

Fuel Tank Capacity	348 l
DEF Tank	19.1 l

AP1055F OPTIONAL EQUIPMENT

OPTIONS

Air-ride Seat with Heat

Auger and Mainframe Extensions

Auxiliary Power Panel

Ballast

Cat Grade Control

Decelerator Pedals

Ecological Washdown System

Feed Sensor (Sonic or Mechanical)

Friction Steering

Hardtop Canopy

HID Lights

Leveling Devices

Lights (Working or Rooding)

Mainframe Extensions (Power or Manual)

Oscillating Push Rollers

Power Folding Front Apron

Product Link

Smooth or Treadbar Belt

Steering Guide

Tow Point Indicators (Upper)

Track Plow

Truck Hitch

Generator

Umbrella

Uptime Kit

Ventilation System

Warning Beacon

Wide-width Paving Packages

Windshield w/Hardtop Canopy

GRADE REFERENCES

Non-Contacting Sonic Grade Sensor

Contacting Grade Sensor

Outboard Leveler, 9.15 m (30') and 12.2 m (40')

Inboard Leveler

Mobile Stringline

Fore 'N Aft Leveler

Sonic Averaging Beam

Rigid Ski, 9.15 m (30') and 12.2 m (40')

SCREED CHOICES

SE60 V Vibratory Screed

SE60 V XW Vibratory Screed

SE60 VT XW Vibratory and Tamper Bar Screed

