



BS 65-V
2 cycle Rammer

The rammer with variable percussion rate and four levels of compaction

The BS 65-V combines all the advantages of the classic two-cycle rammer with the added ability to compact at four different levels. This is achieved by adjusting the stroke height to one of the four levels:

- Level 1: For a smooth finish when repairing asphalt or fitting interlocking paving stones
- Level 2: For accurate compaction and smoothing of compacted edges. Also suitable for sandy soils
- Level 3: For optimum compaction of granular and cohesive soils. Also suitable for gravel, split, slag, lean concrete and ballast
- Level 4: For a particularly dense compaction of cohesive as well as wet soils

**BS 65-V**
2 cycle Rammer

Technical specifications

Operating data

Operating weight	68 kg
Ramming shoe size (WxL) *	280 x 330 mm
L x W x H	673 x 343 x 965 mm
Percussion rate max.	700 blows/min
Stroke	8 mm
Operating speed	9,5 m/min
Surface capacity	159,6 m ² /h

Engine / Motor

Engine / Motor type	air-cooled single-cylinder two-cycle gasoline engine
Engine / Motor manufacturer	Wacker Neuson
Engine / Motor	WM 80
Displacement	80 cm ³
Fuel consumption	0,9 l/h
at rpm	4.400 rpm
Tank capacity	3 l
Gasoline / oil mixture	100:1

* Ramming shoes available in a range of widths.

Information on suitable accessories can be found on our website.

The right to make changes is reserved in the interests of ongoing further developments. You can find more information on the engine power in the operator's manual. The actual power output figures may vary due to specific operating conditions.

Information on suitable accessories can be found on our website. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2013 Wacker Neuson SE.