
SPECIFICATIONS

No. of cylinders / valves		6L / 4
Injection System		ECR
Aspiration		WG / e-VGT
Displacement	liters	8.7
Bore per Stroke	millimeters	117 x 135
Max power	kW (HP) @ rpm	251 (341) @ 2200
Max torque	Nm (kgm) @ rpm	1400 (143) @ 1100
ATS		DOC - p-DPF - SCR - CUC
Certification		Euro VI E

WEIGHT AND DIMENSIONS

Dimensions (L x W x H)	mm	1181 x 1001 x 1079
Dry Weight	Kg	860

DIMENSIONS CAN BE CHANGED ACCORDING TO ENGINE OPTIONS



POWER & TORQUE



IMAGES SHOWN ARE FOR ILLUSTRATION PURPOSE ONLY

Do you want to know more?

- 1	_	-	_	B.II	
- 1-	ᆮ	u	ᆮ	IИ	ν

•	urbc	cnar	ger		

e-VGT (Electronic Variable Geometry Turbo)

2stT (Twin-Stage Turbo)

WG (Fixed Geometry Turbocharger with Waste Gate valve)

Injection System

EUI (Electronically Controlled Unit Injector)

MPI (Multi-Points Injection)

ECR (Electronic Common Rail)

Exhaust System

ATS (Aftertreatment System)

CCDPF (Cross Coupled Diesel Particulate Filter)

CUC (Clean Up Catalyst)

DOC (Diesel Oxidation Catalyst)

SCR (Selective Catalytic Reduction)

p-DPF (Diesel Particulate Filter w/ passive regeneration)

EGR (External Exhaust Gas Recirculation)

HPEGR (High Pressure Cooled External EGR)

FOR INFORMATION ON THE AVAILABLE RATINGS NOT LISTED IN THIS DOCUMENT PLEASE CONTACT THE FPT INDUSTRIAL SALES NETWORK OR VISIT OUR SITE WWW.FPTINDUSTRIAL.COM

SPECIFICATION SUBJECT TO CHANGE WITHOUT NOTICE



