



**CRUSHER TRACK
GCV 80**



TECHNICAL SPECIFICATIONS			
Jaw crusher		type	R 80
Inlet dimensions	mm	815x580	
CSS range	mm	25÷110	
Feeding hopper			
Standard capacity	m ³	6	
Feed height	m	3.85	
Feeder		type	EV 80/2.7
Width	mm	800	
Length	mm	2700	
Main conveyor			
Width	mm	800	
Length	mm	8400	
Engine		type	CAT ° C6.6
Power	kW	130	
Performance*			
Max feed size	mm	450-500	
Production	ton/h	30÷140	
Tracks		tipo	FL6

Transport dimensions			
Length	mm	11900	
Width	mm	2550	
Height	mm	3050	
Weight (excluding options)		kg	24060
Standard equipment:			
Remote control for feeder			
Remote control for tracks			
Options:			
- Side conveyor			
- Overband magnet			
- Dust suppression system			
- Lubricating unit			
- Process monitoring interlocking sensors			
- Hopper extensions			
- Belt protection crusher discharge plate			
- Impact bars in main conveyor charge area			
* Depending on the type and consistency of the feed material, on the pre-screen selected and on the end product required.			

Mobile tracked unit of extraordinary versatility. It can be employed both for crushing demolition debris and for processing tougher and more abrasive materials. The machine can be moved easily and rapidly either inside the working site or from one site to another. Plus, it can be started in a few seconds. The jaw crusher is the sturdiest of its class, with its weight of 8500 kg!

Wide and comfortable walkways, and heat exchanger separated from the engine compartment. The automatic hydraulic jaw adjustment system is the same of bigger models, as well as the handling systems for the production run. The machine is provided with load sensing pumps and last-generation turbo Diesel electronic motor.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV. 04 03/07/2012



REV S.r.l.
Via Marechiese, 66
47864 Pennabilli (RN) - Italy
Tel +39 0541 928474 - Fax +39 0541 928157
<http://www.rev.it> • e-mail: rev.srl@rev.it

