



DPU - 30 kN

Reversible Vibratory Plates (90-280 kg)

Versatile & multi-purpose

The DPU models with 30 kN centrifugal force belong to the class of versatile all around plates, which are ideal for compacting paving stones, horticulture and landscaping, and the maintenance of roads, paths and parking lots. They come with a robust integrated wheel set, like all Wacker Neuson vibratory plates in the 25 - 37 kN class. The machines of this class offer a kind of job site mobility that is unique in the market. Their great agility and compact design make these vibratory plates the perfect choice for continuous use by professionals when compacting sidewalks, trenches and other confined spaces. Different models with three operating widths are available. All come with a multitude of well thought out features:

- That is unique! Integrated and extremely robust wheel set: Even hot asphalt or cumbersome curbs cannot harm the wheels.
- Exceptionally long service life even with the toughest jobs: GJS-700 base plate; the optimal combination of break and wear resistance.
- Guide handle shock mount and integrated lateral guiding systems enable effortless and precise work.
- The automatic locking mechanism of the guide handle has no play, ensuring safe transport.
- Powerful diesel engine with great reserve capacity. Model variations with extra fast advance travel and electric starter available.

**DPU - 30 kN**

Reversible Vibratory Plates (90-280 kg)

Technical specifications

	DPU 3050H	DPU 3050H Elektrostart	DPU 3060H	DPU 3060H-TS
Operating data				
Operating weight kg	181	206	190	190
Centrifugal force kN	30	30	30	30
Base plate size (W x L) mm	500 x 703	500 x 703	600 x 703	600 x 703
Base plate thickness mm	10	10	10	10
Operating width mm	500	500	600	600
Height (without guide handle) mm	758	758	758	758
Frequency Hz	90	90	90	90
Advance travel max. (depending on soil & environmental factors) m/min	21	21	19	23
Surface capacity max. (depending on soil & environmental factors) m ² /h	630	630	684	828
Engine / Motor				
Engine / Motor type	Air-cooled single-cylinder diesel engine	Air-cooled single-cylinder diesel engine	Air-cooled single-cylinder diesel engine	Air-cooled single-cylinder diesel engine
Engine / Motor manufacturer	Hatz	Hatz	Hatz	Hatz
Engine / Motor	1 B 30	1 B 30	1 B 30	1 B 30
Displacement cm ³	347	347	347	347
Engine performance max. (DIN ISO 3046) kW	5	5	5	5
at rpm rpm	3.600	3.600	3.600	3.600
Fuel consumption l/h	0,6	0,6	0,6	0,6
Tank capacity (fuel) l	5	5	5	5
Power transmission	From drive motor via centrifugal clutch and V-belt direct to exciter.	From drive motor via centrifugal clutch and V-belt direct to exciter.	From drive motor via centrifugal clutch and V-belt direct to exciter.	From drive motor via centrifugal clutch and V-belt direct to exciter.



	DPU 3060H-TS Elektrostart	DPU 3070H
Operating data		
Operating weight kg	215	195
Centrifugal force kN	30	30
Base plate size (W x L) mm	600 x 703	700 x 703
Base plate thickness mm	10	10
Operating width mm	500	700
Height (without guide handle) mm	758	758
Frequency Hz	90	90
Advance travel max. (depending on soil & environmental factors) m/min	23	18
Surface capacity max. (depending on soil & environmental factors) m ² /h	825	756
Engine / Motor		
Engine / Motor type	Air-cooled single-cylinder diesel engine	Air-cooled single-cylinder diesel engine
Engine / Motor manufacturer	Hatz	Hatz
Engine / Motor	1 B 30	1 B 30
Displacement cm ³	347	347
Engine performance max. (DIN ISO 3046) kW	5	5
at rpm rpm	3.600	3.600
Fuel consumption l/h	0,6	0,6
Tank capacity (fuel) l	5	5
Power transmission	From drive motor via centrifugal clutch and V-belt direct to exciter.	From drive motor via centrifugal clutch and V-belt direct to exciter.

Information on suitable accessories can be found on our website.

The right to make changes is reserved in the interests of ongoing further developments. You can find more information on the engine power in the operator's manual. The actual power output figures may vary due to specific operating conditions.

Information on suitable accessories can be found on our website. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations.
Copyright © 2013 Wacker Neuson SE.