

Units: US

[Print](#)[Collapse All Specifications](#)**DX210WMH-5****Engine**

Rated Flywheel Power (Gross)	189 hp @ 1,900 rpm
Rated Horse Power (Net)	186 hp @ 1,900 rpm
Max. Torque (Net)	434 lbf-ft @ 1,400 rpm
Engine Emissions Tier (EPA)	n/a

Hydraulic System

Main Pump: Displacement	7.2 in ³ /rev
Control Valve: Relief Valve Pressure (Normal)	5,511 psi
Control Valve: Relief Valve Pressure (Boost)	5,511 psi
Main Pump: Max. Flow Rate (each)	62.3 gal/min
Main Pump: Main Relief Pressure	4,786 psi

Swing Mechanism

Swing Performance: Max Swing Torque	46197 lbf-ft
Swing Performance: Max Swing Speed (At Efficiency)	11 rpm

Travel System/Drive Mechanism

Travel performance: Traction Force (Highest Value)	26742 lbf-ft
Travel performance: Traveling Speed - Low (XXX/)	2.49 mph
Travel performance: Traveling Speed - High (/XXX)	22 mph

Weights

Operating Weight	57,220 lb
Standard Boom Length	25.6 ft
Standard Arm Length	17.7 ft

Dimensions

Wheel Base	10' 10"
Shipping Height - Hose (With Attachment)	11' 4"
Shipping Length (Without Attachment)	31' 3"
Shipping Width (Standard)	8' 2"
Overall Height Over Cab	10' 7"

Working Range

Max Digging Reach (Ground)	35' 9"
Max Digging Depth	16' 4"
Max Loading Height	39' 8"

Refill Capacities

Fuel Tank	79.3 gal
Hydraulic System	76.6 gal
Engine Coolant	6.3 gal
Engine Oil	6.6 gal
Hydraulic Tank	54.16 gal

Environment

Noise Level: Guaranteed Sound Power Level	101 dBA
Noise Level: Operator	70 dBA

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

