




ENDRESS

Power Generators

ESE 3000 BS

Order No. **240209**



Main features

| | |
|------------------------------|----------|
| Alternator type | synchron |
| Max. Output 1~ [kVA/kW] | 2.8/2.8 |
| Continuous Power 1~ [kVA/kW] | 2.5/2.5 |
| Nominal voltage [V] | 230 |
| Nominal Current [A] | 10,9 |
| Power factor cos (phi) | 1 |
| Frequency [Hz] | 50 |
| Protection Class [IP] | 23 |

Engine

| | |
|----------------------------------|--------------------------|
| Design | 1-cylinder. 4-stroke OHV |
| Displacement [ccm] | 193 |
| Output 3000 rpm | 4,9 |
| Fuel | Petrol |
| Fuel tank capacity [l] | 20 |
| Fuel consumption @ 75% PRP [L/h] | 1,4 |
| Running time @ 75% PRP | 14,3 |
| Starting system | Recoil starter |
| Sound power level LWA [db(A)] | 95 |
| Weight in kg ca. | 53 |
| Dimensions L x W x H [mm] | 640 x 475 x 526 |
| Shockproof sockets | 2 x 230V 16A |

This CO₂ measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Equipment features

- Large fuel tank for long running times
- Fuel tank level indicator
- 4 in 1 display for a better overview
- Folding handles
- AVR regulation
- Lack of oil automatic switch-off
- Alternator overload protection

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2020-2-19

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de

