



SCREENING TRACK GSV 45/E



SCREENING TRACK GSV 45/E

TECHNICAL SPECIFICATIONS		
Vibrating screen	type	VN 450/A
Deck dimensions	mm	1500x4500
Number of decks	n.	2
Feed conveyor		
Width	mm	1000
Length	mm	8250
Fines conveyor		
Width	mm	1000
Length	mm	9550
Side conveyor	type	Chevron
Width	mm	650
Length	mm	9000
Side conveyor	type	Chevron
Width	mm	650
Length	mm	9800
Engine	type	CAT® C4 ACERT
Power	kW	94

Performance*		
Max feed size	mm	0-150
Production	ton/h	80÷250
Tracks	type	FL6
Transport dimensions		
Length	mm	11540
Width	mm	2800
Height	mm	3100
Weight (excluding options)	kg	18950
Standard equipment:		
- Remote control for tracks		
- Remote control for feeder		
Options:		
- Automatic lubricating unit		
- Dust suppression system		
- Bottom deck: standard nets, Arpa mesh screens		
* Depending on the type and consistency of the feed material and the end product required.		

Mobile screening unit of great production capacity, particularly suitable for processing very demanding and earthy materials, and for reclaiming and recycling applications. The variable screen angle allows for excellent grading. The wide walkways ensure easy maintenance and

safe operations.

The motor, located at the highest point, is a guarantee for air intake free of dust and process residues. Two-decks vibrating screen that can be supplied with standard nets and special Arpa nets.



The specifications shown in this brochure are not binding. REV reserves the right to make any change without notice.

REV.00 10/07/2012



REV S.r.l.
Via Marechiese, 66
47864 Pennabilli (RN) - Italy
Tel +39 0541 928474 - Fax +39 0541 928157
<http://www.rev.it> • e-mail: rev.srl@rev.it

