



Short Facts

Performance

Max diameter hardwood (in cm) (in cm)	42
Max diameter softwood (in cm) (in cm)	56
Output approx. (in srm)	100
Power requirement (in kW)	100 - 265

Intake opening

Feeding width (in mm)	790
Feeding height (in mm)	610

Grinding unit

Rotor diameter (in mm)	820
Number of blades (half / full equipment) (in cm)	8 (16)

Material outfeed

Blower outfeed	-
Conveyor belt outfeed	-

Main drive

Diesel engine	-
Electric motor	-
(in kW/PS)	-

Carriage

Number of axles	1
Top speed (in km/h)	60

Weight (without crane)

Weight basic model (in kg)	8500
Permitted axle load (in kg)	10000
Permitted support load (in kg)	2000
Permitted total weight (in kg)	12000

Measurements transport position

Length (in mm)	5100
Width (in mm)	2550
Height (in mm)	3600

Control system

easygreen	✓
DIP	✓
Sensotronic	
Automatic overload control unit	✓
Infeed speed stepless adjustable	✓
Wire-remote control	-
15-channel remote control	-
Z-Tronic	✓

HEM 540 Z



Application

- shrubbery and trunk wood up to approx. 560 mm diameter
- driven by PTO shaft with tractors of 100 to 265 kW
- ideal for operation with constricted room
- Ideal machine for smaller orders

Specifics

- smallest mobile chipper driven by PTO shaft from JENZ
- low acquisition and operation costs
- only chipper with uni-axial chassis
- large screening surface for best chip quality

JENZ GmbH Maschinen- und Fahrzeugbau

Wegholmer Str. 14
D-32469 Petershagen

Tel.: +49 (0) 5704/9409-0
E-Mail: info@jenz.de