



## FRONTPAGE

### PRODUCTS

Combi Drills

Trailers

Cranes

Forestry Trailers

Chippers

HJ4

HJ170

HJ250

HJ261

HJ500C

Acid applicators

Product Comparison

## NEWS

## MANUALS

## RECRUITING

## CONTACT

# HJ4

BACK



The Junkkari HJ 4 chipper is especially suited for environmental and landscape chipping.

It is a non-direct feeding chipper, in which the material is fed diagonally into the chippers. The blades draw the wood in themselves, and that makes the work lighter.

The HJ 4 chipper is available as M and G models.

**The HJ 4 M** is equipped with a manual feed chute. It lends itself to chipping branchless trees or trees with few branches.

**The HJ 4 G** is equipped with a hydraulic feeding device. It has one feed roller, and it gets its power from the tractor's hydraulics. The G model requires one pressure valve from the tractor and one return to the feeding device hydraulics. The output needed by the hydraulics system is 20 l/min and pressure a minimum of 140 bar.

The chipper's disc works as a flywheel and ensures even woodchips regardless of changes in the load.

The disk's blades can be adjusted by the required woodchip size. The chipping disk has blow wings, which efficiently spread the woodchips straight into the environment.

### Accessories

- additional blade set (uses 3 blades)
- brush wood blades (uses 3 blades)

### Product Specifications

PROPERTY	HJ4M	HJ4G
Feed opening size, cm	20 x 17	20 x 17
Disc diameter, cm	43	43
Disc mass, kg	45	45
Blade count, kpl	3	3
Revolutions, r/min	540-1000	540-1000
Blade setting, mm	4-12	4-12
Chipping capacity, cm	10	10

Chipping capacity, m <sup>3</sup> /h	2-6	2-6
Power requirement*, kW/hv	10-35/14-50	10-35/14-50
Weight, kg	172	250
Length in working position, cm	125	170
Length in transport position, cm	120	120
Width in working position, cm	150	165
Width in transport position, cm	145	125
Height in transport position, cm	190	190
Hydraulinen syöttövaruste/rullien lkm	lisävaruste	1
Hydr. syöttölaite omalla hydraulikalla	-	-
Torven jatke	-	-
Risuterät laikkaan	lisävaruste	lisävaruste
Risuterät kammioon	-	
No-stress	lisävaruste	vakio (mob)
Kuormainsyöttövarustus	-	-
Yläkammion kippaussylinteri	-	-
Hydr. ylärullan hallinta	-	-
*) Blade adjustment, sharpness, blade setting, and size and type of wood to be chipped have a significant effect on the power requirement.		

JUNKKARI OY  
Pohjanmaanväylä 1720  
FI-62375 YLIHÄRMÄ  
Tel. 010 480 2200  
Fax 010 480 2295  
junnkari@msk.fi  
firstname.lastname@msk.fi

[FRONTPAGE](#) [PRODUCTS](#) [NEWS](#)  
[MANUALS](#) [RECRUITING](#)  
[CONTACT](#)

[EKSTRANET](#)