



## Micro 26™ Electric Scissor Lift

- Compact Size Almost 2 ft. (60 cm) Shorter Than Other 26 ft. (7.6m) Lifts
- 36 in. (90 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive for Extended Duty Cycle, Smoother Control and Fewer Leak Points
- Spacious 2-Person Platform with 500 lb. (226 kg) Capacity
- Driveable at Full Height
- Fully Proportional Lift and Drive Controls

Reach 32 ft. Height in Tight Work Areas  
with Micro Footprint



## Standard Features

### Work Area

Roll Out Deck Extension with Incremental Locking Positions  
 Standard Full Height Swing Gate  
 Lanyard Attachments (2)

### Performance

Direct Electric Drive  
 Fully Proportional Drive and Lift Controls  
 Up To 25% Gradeability

### Power

24v DC, 240 Ah Battery Pack  
 Battery Charge Indicator

### Serviceability

Lubrication-Free Scissor Bearings  
 Easy Maintenance Access to Mechanical and Electrical Components in  
 Swing Out Trays  
 Parking Brake Release Switch for Towing

### Safety

Lift Control Orientation Designed to Avoid Entrapment  
 Dedicated Compartments Protect Electrical and Hydraulic Components  
 Emergency Shut-Off at Platform and Lower Controls  
 Non-Skid Metal Deck Construction  
 Descent Alarm  
 Drive Speed Interlock  
 Multi-Axis Tilt Sensor  
 Multiple Disk Brakes  
 Scissor Maintenance Lock  
 Automatic Parking Brakes  
 Automatic Pothole Protection

### Other Features

Removable Upper Controls  
 Voltage-Compensating Fully Automatic Battery Charger  
 Hour Meter  
 Machine Tie Downs  
 Non-Marking Tires  
 All-Motion Alarm  
 Fork Lift Pockets  
 Flashing Beacon

## Optional Features

900W Inverter  
 Tool Tray  
 Cold Weather Package  
 Proactive Platform Safety System (PPSS)  
 Leak Containment System™ (LCS)  
*Patent Pending*  
 2nd Year Extended Warranty



### MEC Aerial Work Platforms

Tel: 559.842.1500 | 1401 S. Madera Avenue, Kerman, CA 93630 | USA  
 Toll free: 1.877.MEC LIFT | 1.877.632.5438 | Fax: 559.842.1520  
 Email: info@MECawp.com | www.MECawp.com

MEC® is a registered trademark and Micro 26™ and Leak Containment System™ are trademarks of California Manufacturing & Engineering Co., LLC. Leak Containment System™ is Patent Pending. 97024 DTD 0419

Micro 26™	U.S.	Metric
<b>Heights</b>		
Working Height*	32 ft.	9.45 m
Platform Height	26 ft.	7.62 m
Stowed Height (Top Guardrail)	90.3 in.	2.3 m
Stowed Height (Rails Folded)	78.75 in.	2 m
Stowed Height (Platform Floor)	47 in.	1.2 m
Guardrail Height	43.5 in	1.1 m
Toeboard Height	6 in.	0.15 m
Ground Clearance (Stowed)	3 in.	7.62 cm
<b>Dimensions</b>		
Length-Stowed (Overall)	74 in.	1.88 m
Length-Stowed (Ladder Removed)	68 in	1.73 m
Chassis Width	31.9 in	.81 m
Platform Length (Extended)	103.5 in.	2.63 m
Platform Length (Retracted)	68 in.	1.73 m
Roll-Out Deck Length	35.5 in.	.9 m
Platform Width (Outside)	29.1 in.	.74 m
Wheelbase	55 in.	1.4 m
Total Lift Capacity	500 lbs.	227 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs.	113 kg
<b>Speed</b>		
Raise/Lower Speed	30/25 sec	
Drive Speed (Stowed)	2.5 mph	4 km/h
Drive Speed (Elevated)	.5 mph	.8 km/h
<b>Performance</b>		
Gradeability	25% 14 degrees	
Wind Rating	Indoor Only	
Turning Radius (Inside)	6 in.	15 cm
Weight**	4190 lbs.	1900 kg
Power Source	24 v DC, 240 Ah Battery Pack	
Controls	Proportional	
Tires	12 in. x 5 in	30 cm x 12.5 cm

\*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.  
 \*\*Weight may vary with certain options or configurations.

**Important** - MEC scissor lifts must be on a hard level surface while elevated. This machine is indoor rated only.

**Warranty** - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

**Meets or exceeds** the requirements of ANSI A92.20-2018 and CSA B354.6.17.

**Specifications** subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

Distributed by:

