

TECHNICAL SPECIFICATION

| | |
|--------------|---|
| Applications | Tractor / Spreader |
| Description | Multimax MP 515 is a multipurpose radial tire designed for spreaders and utility tractors. The tire shows a unique tread design providing superior riding comfort on the road as well as excellent self-cleaning properties. The strong steel-belted nylon casing ensures extraordinary durability. Multimax MP 515 is made of a special puncture-resistant tread compound providing a longer service life. Speed index class G (90km/h). |

Pattern Name **MULTIMAX MP 515**

| | |
|-----------|-------------------|
| Version | STANDARD |
| Type | TL |
| Tire Size | 445/65 R 22.5 MPT |
| LI/SS | 160 G |

Dimensions (U/M International standard)

| | |
|----------------------------|------|
| Section Width (mm) | 444 |
| Overall Diameter (mm) | 1150 |
| Static Loaded Radius (mm) | 527 |
| Rolling Circumference (mm) | 3532 |
| Rim Rec | 13 |
| Rim Alt | 14 |



LOAD CAPACITY TABLE (kg)

| km/h / bar | 1.6 | 2.0 | 2.5 | 3.0 | 3.5 | 4.0 | 4.5 | 6.0 |
|------------|------|------|------|------|------|------|------|------|
| 90 | 1740 | 2060 | 2410 | 2750 | 3075 | 3390 | 3690 | 4500 |
| 65 | 1890 | 2235 | 2615 | 2985 | 3340 | 3675 | 4000 | 4885 |
| 40 | 2005 | 2365 | 2770 | 3165 | 3540 | 3900 | 4240 | 5175 |