

HIGHLIGHTS

- · Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Torsional Trailing-Arm Independent (TTI) rear suspension
- Front and rear FOX[†] 1.5 PODIUM[†]
- 30 in. ITP † Cryptid † tires
- Intelligent Throttle Control (iTC™) with riding modes
- 14 in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok† QE auto-locking front differential
- · Relocated radiator
- 3,500 lb (1,588 kg) winch
- Heavy-duty front and rear bumpers
- Mud-riding footrests
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- 625 W magneto
- X-package coloration, graphics and seat cover
- Mudguards

SPECIFIC TO VISCO-4LOK PACKAGE

- NEW Visco-4Lok with rider lockable front differential
- Full wrap handguards

ENGINE	850	850 with Visco-4Lok	
Туре	78 hp, Rotax 854 cc V-twin, snorkeled, liquid cooled with relocated radiator		
Fuel Delivery System	Intelligent Throttle Control (iTC) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P/R/N/H/L, standard engine braking		
Drive Train	Selectable 2WD/4WD with Visco-Lok QE auto- locking front differential	Selectable 2WD/4WD/Lock 4WD with Visco-4Lok rider lockable front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar		
Front Shocks	FOX 1.5 PODIUM		
Rear Suspension	Torsional Trailing-Arm Independent (TTI)		
Rear Shocks	FOX 1.5 PODIUM		
TIRES & WHEELS			
Front Tires	ITP Cryptid‡ 30 x 9 x 14 i	ITP Cryptid [‡] 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)	
Rear Tires	ITP Cryptid [‡] 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)		
Wheels	14 in. cast aluminum		
BRAKES			
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers		
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper		



Granite Gray, Black & Manta Green / 850
Neo Yellow & Black / 850 (with Visco-4Lok)

DIMENSIONS & CAPACITIES	850	850 with Visco-4Lok	
Estimated Dry Weight*	990 lb (450 kg)		
LxWxH	88 x 50 x 51.5 in. (224 x 127 x 131 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	13 in. (33 cm)		
Seat Height	36.75 in. (93.3 cm)		
Rack Capacity	Rear: 200 lb (90 kg)		
Storage Capacity	Rear: 5.7 gal (21.4 L)		
Towing Capacity	1,650 lb (750 kg)		
Fuel Capacity	5.4 gal (20.5 L)		

Gauge	7.6 in. wide digital display: Speedometer, tachometer, odometer, trips and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge, clock	
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)	
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light	
Winch	3,500 lb (1,588 kg) winch	
Seat	Standard	
Protection	Heavy-duty front and rear bumpers Mud-riding footrests Mudguards	Heavy-duty front & rear bumpers Full wrap handguards Mud-riding footrests Mudguards

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 36 months



050