H.A.B Model S 152 – 12 E2WD

Features:


- Driveable in full height
- CE certified components
- Fold Down Guard Rails
- User-friendly control system
- Max. stability due to three scissors mechanism
- Unlimited platform capacity on platform and extension
- Narrow design
- All proportional drive, lift and lowering functions

Technical Features

rechnical realures	
Working height	15.20 m
Platform height	13.20 m
Platform size	3.04 m x 1.18 m
Lateral platform extension	1.20 m
Clearance height	2.25 – 2.99 m
Platform capacity	500 kg
Outer turning radius	3.04 m
Inner turning radius	0.06 m
Engine	48 V / 360 Ah
Drive speed in km/h (l/e) *	4.0 0.7
Diesel	-
Lifting time	ca. 75 Sec
Lowering time	ca. 75 Sec
Ground clearance	150 mm
Wheelbase	2.45 m
Max. inclination	3°
Control	Proportional
Greadability	ca. 25%
Weight	4700 kg
Max. ground bearing pressure	71 N/cm ²
Driveable in full height	Yes
External using	No
4 WD	No
4 WS	No
Self-levelling Jacks	Option

1200 15200 13200 н.а.в.

4240



Transport Features Stowed height

Stowed height	2.25 m
Length	5.55 m
Width	1.19 m

*e=elevated; I=lowered



Telefon: +49 (0) 7253 / 94 01 - 0 Telefax: +49 (0) 7253 / 94 01 - 26 service@hab-hubarbeitsbuehnen.de