



ENDRESS

Power Generators

SEA 6

Order No. **151745**

Main features

Alternator type	DUPLEX
Continuous Power 3~ [kVA/kW]	6.0/4.8
Continuous Power 1~ [kVA/kW]	4.0/3.6
Nominal voltage [V]	400/230
Nominal Current [A]	8.7/17.4
Power factor cos (phi)	0,8
Frequency [Hz]	50
Protection Class [IP]	54

Engine

Engine Type	HONDA GX390 / 11 HP
Design	1-cylinder 4-stroke OHV
Displacement [ccm]	389
Output 3000 rpm	6,4
CO2 emissions [g / kWh]	743
CO2 test procedure	k.A
Fuel	Petrol
Fuel tank capacity [l]	33
Fuel consumption @ 75% PRP [L/h]	2,1
Running time @ 75% PRP	15,7
Starting system	Recoil starter
Sound power level LWA [db(A)]	97
Weight in kg ca.	104
Dimensions L x W x H [mm]	780 x 550 x 595
Shockproof sockets	2 x 230V 16A IP 68 1 x 400V CEE 16A IP68

This CO2 measurement results from testing over a fixed test cycle under laboratory conditions a(n) (parent) engine representative of the engine type (engine family) and shall not imply or express any guarantee of the performance of a particular engine'.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2021-2-4

ENDRESS Elektrogerätebau GmbH
Neckartenzlinger Str. 39
D - 72658 Bempflingen, Germany

Phone.: +49 (0) 7123-9737-0
Fax.: +49 (0) 7123-9737-50
www.endress-generators.de



SEA 6

Order No. 151745

Advantages at a glance

- DUPLEXPLUS - the advantages at a glance
- Conforms with the requirements of DGUV Information 203-032
- Operating costs are lowered
- Reduction of the pollutant emissions
- Significantly reduced noise emissions
- Up to 30% less fuel consumption
- Protection Class IP 54 — protected from dust and spray
- Brushless, electronically regulated synchronous alternator
- Voltage stability +/- 1% with 3~ alternators
- Brushless technology - therefore 20,000 operating hours
- 200% Suitable for balanced load in actual operation
- Combines and strengthens the advantages of asynchronous and synchronous generators
- Simultaneous use by electronic and inductive appliances

Equipment features

- ECOTronic system (not required for version IT-TN)
- Honda OHV engines
- 3 in 1 display = V/Hz/h
- Fuel tank level indicator
- Lack of oil automatic switch-off
- Alternator overload protection
- Folding handles
- integrated crane mount
- Control panel with Protection Class IP 54
- A slide compartment for the short operating instructions and a tool is integrated directly under the tank

Possible areas of application*

	400V	230V
Electronic consumers up to	4800W	3600W
Electric tools up to	4700W	3500W
Gardening or construction equipment up to	3200W	2400W
Compressors or pumps up to	2400W	1800W
Inverter welding equipment up to 3.25 mm		

Special equipment - not retrofittable

	Order No.
RCD protection switch incl. earthing kit	162 009
Exhaust hose (1.5 m)	162 333

Accessories

	Order No.
Wheel kit	161 024
Maintenance kit	164 029

garantía alguna ni implícita ni expresa del rendimiento de un motor concreto.

Power ratings according to ISO 8528-1: 2005

Technical data and illustrations are not binding. We assume no liability for misprints.

2021-2-4