

**Tracked Inclined Screen** 



Quality Engineered Excellence Since 1911

## ST225 Tracked 3 Deck Screen 6.7m x 1.5m (22ft x 5ft)













The Parker ST225 triple deck screen is class leading with production capacities and the largest combined screening area available in today's market, the Parker ST225 is the obvious choice for medium to large scale operators who need high capacity and high specification aggregate screening capabilities.

The massive screening area of the  $6.7 \text{m} \times 1.52 \text{m}$  (22ft x 5ft) top and middle decks and the  $6.1 \text{m} \times 1.52 \text{m}$  (20ft x 5ft) bottom deck, in combination with the heavy duty, high energy screening configuration, is specially designed for fine product separation.

- Robust and durable screens featuring rapid setup times
- High volume, high efficiency product screening
- Versatile in a wide range of applications
- Easily accessible maintenance and service points
- Simple hydraulic circuits
- Efficient CATERPILLAR® powerpack designed for low operating cost
- Global aftersales service, support and spare parts supply

## **Options:**

150mm (6") Grizzly Bars
1 or 2 Deck Vibrating Live Head
Dust Suppression System
Radio Controlled Tracks
Overband Magnet
Single Shaft Shredder
Crusher Chute



Feed Hopper Capacity	9.2m³ (12yd³)
Loading Height	3.4m (134")
Grizzly Bar Aperture	100mm (4")
Screen Box Type	3 deck hydraulically driven vibrating screen box
Top Deck Size	6.7m x 1.52m (22' x 5')
Middle Deck Size	6.7m x 1.52m (22' x 5')
Bottom Deck Size	6.1m x 1.52m (20' x 5')
Drive Type	Hydraulic power supplied via PTO
Fines Conveyor Stockpile Height	5000mm (197")
Side Conveyor Stockpile Height	5150mm (203")