

SWE25F Mini Excavator

Operating Weight: 5,820 LBS (2,640 KG)

Gross Power: 20 HP (14.914 kW)

Dig Depth: 8' 10" (2.7 m)



Turn over
for full
specifications!

Technical Specifications and Product Highlights

Machine Dimensions	Machine Weight	5,820 lbs	2,640 kg
	Overall Length	14'	4.26 m
	Overall Height	7' 11"	2.4 m
	Overall Width	4' 11"	1.5 m
	Ground Clearance	11"	280 mm
	Tail Swing Radius	3' 5"	1.05 m
Engine	Brand	YANMAR	
	Model	3TNV80F-SPSU	
	Displacement	.335 Gal	1.267 L
	Output	20 HP	14.914 kW
Working Ranges	Max Speed (High/Low)	2.7/1.6 mph	4.2/2.6 kph
	Bucket Capacity	17 Gal	66 L
	Bucket Width	2'	600 mm
	Max Cutting Height	14' 7"	4.445 m
	Max Loading Height	10' 2"	3.11 m
	Max Digging Depth	8' 10"	2.7 m
	Max Vertical Digging Depth	5'	1.53 m
	Max Digging Reach	15' 11"	4.85 m
	Boom Swing Angle (Left/Right)	66/54 degrees	
	Front Swing Radius	7'	2.14 m
	Tail Swing Radius	3' 5"	1.05 m
	Max Digging Force (Arm)	3.1 kip	14 kN
	Max Digging Force (Bucket)	5.4 kip	24 kN
	Tracks	Swing Speed	9 rpm
Ground Pressure		3.63 psi	25 kpa
Track Width		11.8"	300 mm
Track Length		6' 7"	1.990 m
Track Type		Rubber Crawler	
Gradeability		30 Degrees	
Hydraulics	Brand	KYB	
	Type	1 Variable Plunger Pump	
Fuel and Hydraulics Tanks	Total Flow	20.34 gal/min	77 L/min
	Fuel Tank Capacity	11.2Gal	42.5 L
	Hydraulic Oil Capacity	7.9 Gal	30 L

Dual-Braided hydraulic lines



YANMAR Engine with easy access panels for quick engine maintenance



High-Power standard lights



Enclosed cab offers safety and comfort for extended work hours in tough conditions



Telescopic Chassis gives the operator the ability to navigate tight spaces easily

Sunward USA Corp

Web: www.sunwardusa.com

Address: 2710 Geesling Rd, Denton TX 76208

Contact Info:

Phone: 469-353-6890

Email: info@sunwardusa.com

Model:

SWE25F