

# SUPER PREMIUM 30 DRI



**PATENTED MIXED ROTOR™**  
Equipped with 10 hammers with inserts + 2 blades.




**VERTICALLY GUIDED FEED ROLLER**



**OPTIONAL CO2 REDUCTION**



**30 HP YANMAR**  
liquid cooled 3-CYLINDER DIESEL ENGINE.



**FLARED HOPPER WITH CONVEYOR FEED (STANDARD – WIDTH 25 CM)**



**180° CHIMNEY**  
Fitted with a simple and effective rotation system.

## TECHNICAL CHARACTERISTICS

Art number	1425446
Engine	YANMAR 3TNV76 / 30 hp / 22,06 kw
Engine swept / volume cm <sup>3</sup>	1116 / 3-cyl.
Fuel	Diesel
Cowling	DRI soundproofing
Admissible diameter	15 cm
Output	22 m <sup>3</sup> /h
Rotor diameter	560 mm
Rotor weight	80 kg
Hammers	10
Knives	2
Feeder	1
Feed roll width	250 mm
Feed roll diameter	340 mm
Allowable road weight axles	1 800 kg
No. of axles	1
Tyre dimensions	145 x 13
Tank capacity	30 L
Consumption	3,2 L/h
Multidirectional chimney	180 °
Chimney outlet height	2 100 mm

Machine weight	1 260 kg
PTAC trailer approval	1 300 kg
Hopper dimensions (L x W)	1 600 x 1 400 mm
Hopper loading height	700 mm
L x W x H	4 100 x 1 650 x 2 300
Guaranteed acoustical power level rating	124 dBA

## OPTIONS

Option CO2 Reduction	1425209
Insert ref.	RHEV/0010 (10)
Knife ref.	RHEV/0020 (2)
Spare wheel ref + spare wheel support ref.	1425925
Wheel chock ref. (2)	ECIPRE/0010
Stabilizer legs ref.	ECIMV/0325

Machine directive : 2006/42/CE.

Harmonized standards used : EN 13525.



TS INDUSTRIE GmbH  
Weserstrasse 2 - 47506 NEUKIRCHEN-VLUYN  
DEUTSCHLAND  
Telefon +49(0)2845 9292-0  
Telefax +49(0)2845 9292-28  
kontakt@ts-industrie.eu

[www.ts-industrie.eu](http://www.ts-industrie.eu)