

T650

Loaders

Specifications

Į	VI	a	C	h	iı	n	е	F	≀a	ti	n	C

Rated operating capacity (ISO 14397–1) Tipping load (ISO 14397-1) 1242 kg 3550 kg 87.10 L/min Pump capacity Pump capacity (with high flow option) 126.90 L/min System relief at quick couplers 23.8-24.5 MPa Max. travel speed 10.6 km/h

Engine

Make / Model Bobcat / D24 Compliancy 97/68 EC Stage IIIB Fuel Diesel Cooling Liquid Power (SAE J1995) at 2600 RPM: 56.0 kW Torque at 1800 RPM (SAE J1995 Gross) 283.9 Nm Number of cylinders Displacement 2392 cm³ Fuel tank 104.10 L Weights

Operating weight 4445 kg Shipping weight 4107 kg

Controls

Vehicle steering Direction and speed controlled by two hand levers or joysticks (optional) Separate foot pedals, optional Advanced Control System Loader hydraulics tilt and lift

(ACS) or Selectable Joystick Controls (SJC) Front auxiliary (standard) Electrical switch on right-hand steering lever

Drive System

Transmission Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors

Lift arm support

Parking brake

CE certification

Seat belt

Seat bar

Work lights, front and rear

Tracks — rubber — 450 mm

Turbo-charger with approved spark arrestor

Warranty: 12 months or 2000 hours, whichever occurs first

Standard Features

Adjustable suspension seat Automatically activated glow plugs

Auxiliary hydraulics: variable flow/maximum flow Bob-Tach™ frame

Bobcat Interlock Control System (BICS)

Whole body vibration (ISO 2631-1)

Hand-arm vibration (ISO 5349-1)

Deluxe operator cab* - Includes interior cab foam, side, top and rear windows, cab door with windshield wiper and sensor, Deluxe wire harness, dome light, electrical power port, cup holder, storage compartment and horn

Electrically activated proportional front auxiliary hydraulics Engine/hydraulics system shutdown

Hydraulic bucket positioning (including ON/OFF switch) Instrumentation

* Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I


Options

Deluxe instrument panel Two speed Power Bob-Tach™ Air ride seat with 2 point seat belt Cab enclosure with heating Air ride seat with 3 point seat belt Air conditioning Back-up alarm Advanced Control System (ACS) Beacon Selectable Joystick Controls (SJC) Engine block heater Roller Suspension™ Fire extinguisher High flow hydraulics Strobe **Environmental** Operator LpA (98/37 & 474-1) 85 dB(A) Noise level LWA (EU Directive 2000/14/EC) 103 dB(A)

0.54 ms⁻²

1.61 ms⁻²

Dimensions



Attachments

Angle Brooms Augers Backhoes Bale Forks Box Blades Breakers Brushcat™ Rotary Cutters **Brush Saws Combination Buckets** Concrete Mixers Concrete Pumps Construction / Industrial **Buckets** Dozer Blades **Drop Hammers** Dumping Hoppers Fertilizer and Grain Buckets Flail Cutters Graders Grapples, Industrial Landplanes Landscape Rakes Laser Equipment Low Profile Buckets Mixing Buckets Packer Wheels

Pallet Forks, Hydraulic

Pallet Forks, Standard

Planers Rear Stabilizers Root Grapples **Rotary Grinders** Scarifiers Scrapers Skeleton Buckets Snow & Light Material **Buckets** Snow Blades Snow Blowers Snow Pushers Snow V-Blades Soil Conditioners Spreaders Stump Grinders Sweepers Tillers Tree Transplanters Trench Compactors Trenchers Utility Forks Vibratory Rollers Water Kits Wheel Saws Whisker Brooms Wood Chippers