## ROLLANT

P. de un		355 RC Uniwrap*	355 RC Comfort	355 RC	354 RC	354
Pick-up Width		2.10	2.10	2.10	1.85 / 2.10	1.85 / 2.10
DIN raking width	m	1.90	2.10	1.90	1.65 / 1.90	1.65 / 1.90
	m	0	0	0	0	0
Roller crop press Ground tracking via two oscillating pick-up castor guide wheels		•	•	•	•	•
Ground tracking via two oscillating pick-up castor guide wheels			•		•	
Hydraulic connection						
Single-acting spool valve for pick-up lift / dual-acting spool valve for tailgate cylinders		_	_	•	•	•
Single-acting spool valve and open return line		•	•	_	_	_
Crop feed						
Rotor		ROTO CUT	ROTO CUT	ROTO CUT	ROTO CUT	Heavy Duty ROTO FEED
Number of knives		16	16	16	16	_
ROTO RESERVE (2nd additional spool valve required)		•	•	0	0	0
Bale chamber						
No. of compaction rollers		16	16	16	16	16
Automatic chain lubrication		•	•	•	•	•
Autolube for baler bearings		0	0	0	0	0
Air brakes*		•	0	0	0	0
Hydraulic brakes*		•	0	0	0	0
Active hydraulic brake system*		•	0	0	0	0
Bale ejector		_	•	•	•	•
Baling chamber dimensions						
Width	m	1.20	1.20	1.20	1.20	1.20
Diameter	m	1.25	1.25	1.25	1.25	1.25
Diamotor		1.20	1.20	1.20	1.20	1.20
Control terminal						
CLAAS Medium Terminal (CMT)*		_	_	•	•	•
CLAAS COMMUNICATOR*		•	•	•	_	_
Weener						
Wrapper Film stretcher	mm	2 x 750	_		_	_
Stretch film store		12 rolls	_	_	_	_
Overlap		52%	_	_	_	_
Pre-stretching		67% (82% O)	_	_	_	_
Turco						
Tyres 15.0/55 R 17 10 PR		_	•	•	•	•
Tyres 19.0/45 R 17 10 PR			0	0	0	0
Tyres 500/45 R 22.5 12 PR		_	0	0	0	0
Tyres 560/45 R 22.5 8 PR		•	-	-	_	-
Dimensions and weights			4.70	4.70	4.70	4.70
Length	m	6.69	4.72	4.72	4.72	4.72
Width	m	2.98	2.58 – 2.77	2.33 – 2.77	2.33 – 2.77	2.33 – 2.77
Height	m	2.83	2.31	2.31	2.31	2.31

## **Optional equipment**

ISOBUS connection cable, spotlights, load sensing

\* Depending on country specification. ROLLANT 355 UNIWRAP not available in UK.

CMT = CLAAS MEDIUM TERMINAL

• Standard • Optional – Unavailable

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed for photographic purposes in order to present the function clearly. To avoid any risk of danger, never remove these protective panels yourself. In this respect, please refer to the relevant instructions in the operator's manual.

Specifications