

TRAKPACTOR 500SR

The Powerscreen® Trakpactor 500SR is a horizontal shaft impactor which is versatile, efficient and highly productive. It offers both excellent reduction and a high consistency of product yield in quarrying, recycling and demolition applications.

The Trakpactor 500SR features a screen recirculating conveyor which returns oversized product to the crusher for further reduction and a double deck post-screen for fine-sizing providing operators with highly specified material sizes.

Features & Benefits

- Suitable for a variety of feed materials including recycling, demolition & quarry applications
- Load management system to control feeder speed
- Double deck grizzly feeder with under screen
- Impact crusher with hydraulic overload protection
- 4 Bar rotor with twin apron design
- Crusher speed variation through user friendly PLC control system
- Modular conveyor with raise/lower facility to aid clearance of rebar
- Economical to operate with a chamber drive via clutch & highly fuel efficient direct drive system
- Hydraulically folding recirculation conveyor, no crane required during set-up
- Full length conveyor "under belt version"
- Fitted with Powerscreen Pulse Telematics system

Options

- Full & half size martensitic, austenitic, chrome, ceramic blow bars
- Vibrating grizzly feeder
- 4 Full size blow bars in lieu of 2 full 2 half blow bars
- Blow bar crane
- Wire mesh for grizzly underscreen
- Optical belt scale
- Single pole/twin pole magnet
- Dirt conveyor
- Electric refuelling pump
- Hydraulic driven water pump
- Radio remote control
- 2 Deck live pre-screen
- Single deck post-screen
- Plant lighting
- Fully independent under crusher vibrating pan feeder

Applications

- Blasted rock
- River rock
- C & D waste
- Foundry waste
- Processed ores
- Processed minerals

TRAKPACTOR 500SR

Weight (Est)	67,000kg (147,710lbs) without side conveyor or magnet
Transport width	3.18m (10'5")
Transport length	18.6m (61'1")
Transport height	3.8m (12'6")
Working width	7.1m (23'4") with side conveyor
Working length	20.7m (67'11")
Working height	5.47m (17'11")



*Depends on application
Engines are available that are certified to US EPA and EU off road diesel emission standards. Talk to your dealer about possible certification options (i.e. Tier 3/Stage 3A, Tier 4/Stage 3B, Tier 4F / Stage 4).

