

Technical specifications PL 1760



(Perfectly fitting front linkages or 3-point point hitch, fork-lift, construction equipment, ...)

Standard equipment

1 blade with safety release facility
Depth skids
Mechanical swivel device 30°
Steel wear bar 150 x 15 mm, screwed
Signal flags

Series

Overall width
Operating width
Blade height - centre
Blade height - side
weight

UNI-150

1500 mm
1250 mm
750 mm
860 mm
300s kg

Accessories

Hydraulic swivel device 30° PL 1783
Wheels, diam. 200 mm, *when ordered with blade* PL 1555
Wheels, diam. 200 mm, *separate delivery* PL 1556
Hydraulic pivoting device PL 1786

Adaptor for snow blade - series Universal

Adaptor for 3-point front linkage, cat. 2 PL 1775
Adaptor for 3-point rear linkage, cat.1 and cat.2 PL 1776
Adaptor for front-end loader Eurokipp with quick-change plate (*incl. pivoted compensation*) PL 1777
Adaptor for front-end loader Ökonom and Universal PL 1778
Adaptor for self-assembly to third-party front-end loaders (*straight traverse, width approx. 1,20m*) PL 1779
Adaptor for forklift PL 1780
Adaptor for quick coupling triangle (Weiste-triangle) PL 1781
Adaptor for construction machinery (JCB, etc.) PL 1782

