



Also available  
as an  
OFF-ROAD version!

# Tractor chipping machine WT 10 Z

## Maximum output guaranteed!



**In areas of application where conventional mobile chipping machines reach their limits, the WT 10 Z only just starts to warm up.**

**Chipping output: max. 160 m<sup>3</sup>/hour**

**Feed opening (w x h): 98 x 71 cm  
Tree diameter: max. 70 cm**



# Optimum output and user-friendliness!

This versatile, mobile chipping machine devours thick end pieces as well as shrubbery (residual wood left after cutting). The WT 10 Z is very easy to manoeuvre and produces coarse G50 chopped material with square wood chips for heat-generating stations. This chipping machine produces a very small portion of fines in the chopped material and so very little fine dust. When you change the screen (5 min) and the feed, you can produce high-quality G30 chopped material for small heating systems.



## Technical data WT 10 Z

Feed opening (w x h)	cm	98 x 71
Tree diameter	max. cm	70
Chipping output up to max.	m <sup>3</sup> /hour	160
Chipping knives	units	12
Discharge height	max. m	5.2
Horizontal conveying	max. m	8
Machine length	m	5.8
Machine width	m	2.5
Dead weight w/o crane from	t	10.5
Dead weight with crane from	t	13
Feed chain/Roller length	m	1.1 or 2.7
Power requirement tractor	HP	270-400
Chassis with 2 axles		4 wheels, w 445/h 900



## Arguments that carry conviction

- **First-rate heavy-duty blower:**  
Discharge output adjustable, wear plates of different size can be used.
- **First-rate automatic reverse system:**  
Danfoss PVG hydraulic valve for automatic reversing system for feed conveyor.
- **First-rate sensor:**  
Speed sensor on the blower, faster switching response, easy on the V-belt drive on the blower.
- **First-rate electronic box:**  
Process control CAN BUS system for all functions (no relays and contactor box controls).
- **First-rate performance:**  
large tractors with up to 400 HP serve as drives.
- **First-rate feed:**  
Planetary drive in the upper roller, aggressive feed for shrubbery and residual wood left after cutting.
- **First-rate feed conveyor:**  
Length: 2.7 m - swivelling for transport position.
- **First-rate ejector:**  
All functions electric, cyclone - dust-free chipping.
- **First-rate bottom connection:**  
Improved traction of the tractor.
- **First-rate chassis:**  
Spring-loaded axles, extra-wide tyres, easy to manoeuvre in the forest.
- **First-rate screen change:**  
Remove 3 screws, 5 minutes' work, continue chipping. Can be turned round if worn.



All our equipment and machinery are constantly tested and further developed. Subject to technical alterations and output data changes without notice.  
© 2008 by MUS-MAX/Austria - photographs: MUS-MAX.at