Pegson XA400S & Pegson XR400S



The Powerscreen® Pegson X400S range of high performance primary jaw crushing plants are designed for medium scale operators in quarrying, demolition, recycling and mining applications. The range includes the Pegson XA400S with hydraulic adjust and the Pegson XR400S with hydraulic release. User benefits include track mobility for a quick set-up time (typically under 30 minutes,) hydraulic crusher setting adjustment for total control of product size and crusher overload protection to prevent damage by uncrushable objects.

Features & Benefits

- High output and excellent reduction capability
- Hydraulic folding feed hopper with boltless fixing system
- Excellent under crusher access with a hydraulic tilting conveyor system
- Economical to operate with a highly fuel efficient direct drive system
- Forceful crushing action with high swing jaw
- Height adjustable product conveyor
- Extended hopper hydraulically folding

Options

- Deflector plate under crusher
- Dirt conveyor
- Single pole/twin pole magnet
- Radio remote control
- Belt weigher
- Electric refuelling pump
- Hydraulic water pump
- Underscreen wire mesh: 10, 20, 30, 40 or 50mm

Output Potential: up to 400 tph (441 US tph)*

Pegson XA400S	
Weight (Est)	44,750kgs (98,656lbs)
Transport width	2.8m (9'2")
Transport length	15.2m (49'10")
Transport height	3.4m (11'2")
Working width	4.3m (14'1")
Working length	15m (49'3")
Working height	4.1m (13'5")

Pegson XR400S	
- ·	44.7F0(co./00.0F0(bo)
Weight (Est)	44,750kgs (98,656lbs)
Transport width	2.8m (9'2")
Transport length	15.2m (49'10")
Transport height	3.4m (11'2")
Working width	4.3m (14'1")
Working length	15m (49'3")
Working height	4.1m (13'5")

